



Rowa Vmax™ 160

Technical data

Dimensions	Width	1.63 m		
	Height	1.70–3.50 m (in 5 cm intervals)		
	Length	2.68–15.17 m (in 48 cm intervals)		
Sound level	Average sound pressure level Lp,m	48.3 dB (A)		
Possible locations	Ground floor, basement, upper floor			
Input and output times	Input	Approx. 3 seconds (Direct availability for over-the-counter sales)		
	Output	Approx. 8 – 12 seconds (several packages at the same time possible)		
Storable package sizes	Square packages	Min. package size (D × W × H)	35 × 15 × 15 mm	
		Max. package size (D × W × H)	230 × 140 × 145 mm	
		Weight	5–1,000 g	
	Round packages	Min. package size	Ø 45 mm, height: 15 mm	
		Max. package size	Ø 140 mm, height: 145 mm	
		Weight	5–800 g	
Barcodes	Identification and reading of PZN, PZN8, EAN, and 2D barcodes			
Electrical Parameter	8 A, 230 V, 50/60 Hz			
Power consumption	In operation	650 W with one picking head		
		780 W with two picking heads		
	In standby mode	348 W with one picking head		
		379 W with two picking heads		
Safety	System protection thanks to uninterrupted power supply (UPS), backup computer, remote monitoring			
Options	2 nd picking head	2 nd Input belt	Rowa™ Label (labeling)	
	Rowa cleaning module	Rowa System backup	Rowa ProLog™ external (fully automatic input)	
	Rowa refrigerated unit	Rowa MedPort	Rowa iProLog™	
Conveyor technology	Conveyor belt, servo controlled lift, spiral chute with Ø 400 mm, possible to connect up pneumatic tube transport			
Colors	White (RAL 9016), anthracite (RAL Design 000-25-00)			

Becton Dickinson Rowa Germany GmbH, RowastraÙe, D-53539 Kelberg
+49 2692 92 06 0 tel, +49 2692 92 06 1299 fax

bd.com/rowa

